




45-BS STATIC OFFLINE FILTER SYSTEM



DIMENSIONS







FEATURES

Include:

- Automatic low pressure cut-off
- Integrated sample points

BENEFITS

System benefits include:

- Removes microparticles
- Removes free and dissolved water contamination
- Increases system reliability
- Prevents system corrosion
- Reduces component wear
- Extends oil life and generates CO₂ saving
- Reduces operating costs

APPLICATION EXAMPLES

Suitable for the following Industrial applications:

- Earth moving machines
- Forestry equipment
- Mobile cranes
- Drilling/piling equipment
- Static hydraulic systems

Max Op Temp	IP Rating	Flow Rate (I/h)	Pump Suction Lift	Voltage	Current Draw	Power	Dimensions (mm)		Weight (kg)	Filter Retention Element Capacity (per set) Type		
lemp			LIII				Н	W		туре		
60°C	IP55	500	Self- priming to 5.5 metres	230V	5 Amps	0.55kW	591 80	713 69	95	Standard fit: 4 x SDFC	≤ 10 kg Dirt	≤ 3.12 Litres of water

Note: Flow rates, oil cleanliness levels and moisture removal results are based on ISO VG 46 Mineral Oil @ 40° C



ETL Fluid Experts Ltd

Grimbald Crag Road, Knaresborough North Yorkshire, HG5 8PY

> T +44 (0)1423 522911 E sales@etlfe.com

www.etlfluidexperts.com